



Alpha Miner PSU-7KBM19 Specifications

OUTPUT 1	VDC	12V - 15.5V
	Rated Current (220V input)	450A
	Rated Peak Power (220V+ input)	7200W
	Rated Operational Power (220V+ input)	7000W
	Ripple & Noise	<1%
	Source Regulation	<1%
	Load Regulation	<1%
	Setup, Rise Time	<2S
	Power off Protection Trip Time	>10mS
OUTPUT 2	DC voltage	12.3
	Rated Current (220V input)	15A
	Rated Power (220V input)	150W
	Ripple & Noise	<1%
	Voltage Accuracy	12.2V - 12.4V
	Source Regulation	<1%
	Load Regulation	<1%
	Setup, Rise Time	<2S
	Power off Protection Trip Time	>10mS
AC INPUT	Input Voltage, VAC	200-300
	Frequency Range	47-63Hz
	Power Factor (Full Load)	>0.99
	Leakage Current (220V 50 Hz)	<1.5mA
PROTECTIONS	Under Voltage Protection (UVP)	180 VAC
	Short Circuit Protection (SCP)	Yes
	Over Temperature Protection (OTP) (air)	Yes, up to 45°C ambient
	Over Current Protection (OCP)	366A-466A
OPERATIONAL ENVIRONMENT	Operational Temperature Range (air)	-20-45°C
	Operating Humidity, RH (non-condensing)	20%-90%
	Altitude	< 2000 m
DIMENSIONS	Size, mm	255 x 252 x 63
	Net Weight, Kilos	3.8
OTHER	Cooling: Forced Air / Dielectric Fluid	Yes / Yes
	Noise (air)	68 dBA

📍 30 N. Gould Street, Ste. 7253, Sheridan, WY 82801, USA

 alphaminer.io

